Monitoring to associate a plume of MTBE in Groundwater with a vapor release


John Wilson and Jack Hwang
U.S. EPA
Mark Miller, Alex Wardle
and Randy Chapman
Virginia DEQ
OS EPA Region III Lust Technic


2006 EPA Region III Lust Technical Conference, Roanoke, Virginia

April 4, 2006

RESEARCH AND DEVELOPMENT


Building a scientific foundation for sound environmental decisions

















SOURCES: 7-ELEVEN FILE IT CORP. DRAWNGS 822662005, 822662007, AND 802078007







Concentration of MTBE MW-2










SOURCES: 7-ELEVEN FILE IT CORP. DRAWNGS 822662005, 822662007, AND 802078007







Concentration of MTBE MW-6










SOURCES: 7-ELEVEN FILE IT CORP. DRAWNGS 822662005, 822662007, AND 802078007






Concentration of MTBE MW-5






Water Vapor Condenses






MTBE Vapors Escape UST






MTBE Vapors Dissolve in Condensate





MTBE in Ground Water in Tank Fill Material





Activities

- install a device in the vaults surrounding suspected sources of gasoline vapors that that emits vapors of deuterium oxide D₂O (heavy water) at a slow rate over time
- install in the vaults devices that measures the concentration of MTBE vapors and D₂O vapors



Activities

- determine the concentration of MTBE vapors in the vault above the tank
- determine the concentration of D₂O in water vapors in the vault above the tank
- determine the concentrations of MTBE and D₂O in water in the ground water around the tank



Activities

Based on the concentration of D₂0 and MTBE vapors in the vaults, compared to the concentrations of D₂O and MTBE dissolved in ground water in the tank fill, determine whether particular potential sources are plausible causes of the MTBE in the ground water.



Passive Diffusion Samplers for MTBE Vapors
















Passive Diffusion Samplers for Water Vapor and D₂O Vapor








Source of D₂O Vapor









RESEARCH & DEVELOPMENT












MTBE in Ground Water in Tank Fill Material






















































We emplaced 15 liters of D_2O .

We recovered 2 liters in D₂O in the ground water in the tank fill.



Activities

Based on the concentration of D₂0 and MTBE vapors in the vaults, compared to the concentrations of D₂O and MTBE dissolved in ground water in the tank fill, determine whether particular potential sources are plausible causes of the MTBE in the ground water.



mole ratio D/H in standard = 0.000156

$$\delta D\% = \boxed{ \begin{aligned} &\text{Fraction D}_{\text{sample}} \text{-} &\text{Fraction D}_{\text{standard}} \\ &\text{Fraction D}_{\text{standard}} \end{aligned}} \quad *1000$$

$$\Delta \delta D_{\text{sample}} = \delta D_{\text{sample}} - \delta D_{\text{background}}$$



Additional $D_{condensate}$ = Additional $D_{tankfill}$

Where K = 1000 * mole ratio D/H in standard:

Additional $D_{tankfill} = K * \Delta \delta D_{tankfill} * Volume_{tankfill}$

Additional $D_{condensate} = K * \Delta \delta D_{condensate} * Volume_{condensate}$

 $Volume_{condensate} = \Delta \delta D_{tankfill} * Volume_{tankfill} / \Delta \delta D_{condensate}$



Total MTBE_{condensate} = Total MTBE_{tankfill}

Total MTBE_{tankfill} = Conc. MTBE_{tankfill} * Volume_{tankfill}

Total MTBE_{condensate} = Conc. MTBE_{condensate} * Volume_{condensate}

Expected Conc. MTBE_{condensate} =

Conc. MTBE_{tankfill} * Volume_{tankfill} / Volume_{condensate}



The evaluation will be expressed as the ratio of the measured concentration of vapors in each vault to the concentration of vapors necessary to explain the MTBE in the ground water in the tank fill.




Date recovered	MTBE (ug/L water)	Deuterium in Water Vapor (δD‰)	Deuterium in Water Vapor %(H+D)
Regular Dry Break			
12/16/2005	9590	38,037	0.60
1/19/2006	4941	2,522,112	28.20
2/16/2006	3827	68,320	1.07



Date	MTBE	MTBE	Ratio
recovered	measured	required	measured to
	(ug/L water)	(ug/L water)	required
Regular Dry Break			
12/16/2005	9,590	6,188	1.55
1/19/2006	4,941	410,322	0.01
2/16/2006	3,827	11,115	0.34





Location	Date recovered	Ratio measured to required
Mid-Grade ATG	12/16/2005	0.09
Mid-Grade ATG	1/19/2006	0.02
Mid-Grade ATG	2/16/2006	0.04



Location	Date recovered	Ratio measured to required
Mid-Grade Dry Break	12/16/2005	0.33
Mid-Grade Dry Break	12/16/2005	0.91
Mid-Grade Dry Break	1/19/2006	0.00
Mid-grade Dry Break	2/16/2006	0.13



Location	Date recovered	Ratio measured to required
Mid-Grade Sump	12/16/2005	0.14
Mid-Grade Sump	12/16/2005	0.05
Mid-Grade Sump	1/19/2006	0.03
Mid-Grade Sump	1/19/2006	0.02
Mid-grade Sump	2/16/2006	0.03
Mid-grade Sump	2/16/2006	0.02



Location	Date recovered	Ratio measured to required
Premium ATG	12/16/2005	0.93
Premium ATG	1/19/2006	0.02
Premium ATG	2/16/2006	0.01



Location	Date recovered	Ratio measured to required
Premium Dry Break	12/16/2005	0.26
Premium Dry Break	1/19/2006	0.01
Premium Dry Break	2/16/2006	0.01



Location	Date recovered	Ratio measured to required
Premium Sump	12/16/2005	0.03
Premium Sump	12/16/2005	0.00
Premium Sump	1/19/2006	0.01
Premium Sump	1/19/2006	0.02
Premium Sump	2/16/2006	0.01
Premium Sump	2/16/2006	0.01



Location	Date recovered	Ratio measured to required
Regular ATG	12/16/2005	0.02
Regular ATG	1/19/2006	0.03
Regular ATG	2/16/2006	0.02



Location	Date recovered	Ratio measured to required
Regular Dry Break	12/16/2005	1.55
Regular Dry Break	1/19/2006	0.01
Regular Dry Break	2/16/2006	0.34



Location	Date recovered	Ratio measured to required
Regular Sump	12/16/2005	0.00
Regular Sump	12/16/2005	0.01
Regular Sump	1/19/2006	0.01
Regular Sump	1/19/2006	0.01
Regular Sump	2/16/2006	0.15
Regular Sump	2/16/2006	0.03





